



ELECTRIC TOOL LIFT (ETL-350)
BID SPECIFICATION
REVISED: September 6, 2022

Type:	Vanair® ETL-350 electric power tool lift. New and in current production.
Power Supply:	Linear Actuator: 12 VDC ball screw motor with 30 AMP maximum current draw.
Maximum Stroke Speed:	2.7 inches per second.
Temp Range:	-20 ° to 150 ° F, IP65 Rated
Operating Voltage Range:	10 to 16 VDC (ratings at 12 VDC normal) with a built-in thermal overload control.
Weight:	150
Lifting Capacity:	350 Lbs.
Dimensions:	Height: 33.0" Width: 17.5" Depth Folded: 16.5" Max Reach: 27.25" Max Drop: 19.0" Drop Edge: 17.37"
Mainframe:	Fully powder-coated paint protection, all pivot points fit with oil-lite bushings.
Warranty:	The unit shall be warranted for 1 year against defects in materials and workmanship and against the loss of capacity due to wear. The unit will be replaced or repaired at Vanair®'s option as a result of such defects. This warranty does not cover damage caused by accident, misuse, or negligence. If the unit is disassembled the warranty is void.
Features:	Three Integrated tool holder positions Integrated limit switches Various hex tool posts ranging from 7/8" to 1 -1/4" Integrated actuator brake allows load to be stopped in any position Safeties: integrated actuator overload clutch, safety latch, and integrated safety shutoff switch