
Type:	Vanair® PRO 35 Series. New and in current production.
Compressor:	Reciprocating type. 2 cylinders, single stage, splash lubricated, “NPT ball valve/tank models”, M-JIC skid units, steel braided discharge line, automatic throttle control with unloader valve.
Compressor Capacity:	35 CFM up to 175 PSIG
Engine:	Single cylinder, electric or pull start, gasoline engine, Honda® 11HP GX390.
Fuel Capacity:	1.6 gallon Honda.
Air Storage Tank:	30-gallon air tank. ASME/CRN certification on appropriately sized tanks. Unit to include pressure gauge, ball valve, pressure relief valve, and condensation drain.
Weight:	Dry weight (Lbs.): 460.
Dimensions:	47L x 19W x 43H (In.)
Drive System:	Classic V-belt drive system.
Metal and Tanks:	Fully powder-coated belt guard, 3/16 plate steel main frame, full-service access.
Warranty:	The air compressor shall be warranted for three (3) years when following the prescribed maintenance schedule. This warranty does not cover damage caused by accident, misuse, or negligence. If the unit is disassembled the warranty is void.
Service Centers:	Manufacturer MUST have factory authorized service centers located in each state of the United States of America and Canadian provinces.
Options:	Vibration Isolators Maintenance Kits Battery Kits