

## PRO 25 SERIES RECIPROCATING AIR COMPRESSOR

BID SPECIFICATION REVISED: December 20, 2024

Type: Vanair® PRO 25. New and in current production.

Compressor: Reciprocating type. 3-cylinder, single stage, splash lubricated, "NPT ball valve/tank models",

steel braided discharge line, automatic throttle control with unloader valve.

Compressor

Capacity: 25 CFM and up to 175 PSIG MAX.

**Engine**: Single cylinder, electric or pull start, gasoline engine, Honda<sup>®</sup> 8.4 HP GX270.

Fuel Capacity: 1.4 gallons.

Air Storage Tank: 30-gallon air tank. ASME/CRN certification. Unit to include pressure gauge, ball valve, pressure

relief valve, and condensation drain.

Weight: Wet weight (Lbs.): 303., Dry weight (Lbs.): 290.

**Dimensions**: 42.7L x 17.6W x 41.1H (ln.)

**Drive System**: Classic V-belt drive system.

Metal and Tanks: Fully powder-coated belt guard, 3/16 plate steel main frame, full-service access.

Warranty: The air compressor shall be warranted for three (3) years when following the prescribed

maintenance schedule. This warranty does not cover damage caused by accident, misuse, or

negligence. If the unit is disassembled the warranty is void.

Service Centers: Manufacturer MUST have factory authorized service centers located in each state of the United

States of America and Canadian provinces.

Options: Maintenance Kits