



AIR N ARC® 150
ALL-IN-ONE POWER SYSTEM®
**14 HP RECIPROCATING AIR COMPRESSOR/
WELDER/GENERATOR/BATTERY BOOSTER**
BID SPECIFICATION
REVISED: May 27, 2025

Type:	Vanair® Air N Arc® 150 Series. New and in current production.
Welder:	40-150 AMPs operating range. Patented amperage and power controls built into welding leads. 20 ft. welding leads included and required for welding operation.
Generator:	Totally brushless with capacitor, copper windings, bi-directional rotation, <4% distortion.
Generator Capacity:	5 kW peak, 4.2 kW continuous, AC power, 60 Hz, single phase, 120V and 240V outlets.
Compressor:	Reciprocating type. 3-cylinder, single stage, splash lubricated, with built-in head unloaders, steel braided discharge line and automatic throttle control.
Compressor Capacity:	20 CFM and up to 150 PSIG. (Factory set to 125 PSI).
Battery:	12V sealed lead acid – Per DOT specification 49 CFR 173.159
Engine:	Single Cylinder, electric start gasoline engine, Kohler® model Command PRO CH440, air cooled, 14 HP per SAE J1940 specification and automatic electronic throttle control.
Fuel Capacity:	1.9 gallons
Air Storage Tank:	Options for 10 gallon, 30 gallon, or remote air tank. ASME/CRN certification on appropriately sized tanks. Unit to include pressure gauge, ball valve, pressure relief valve, and condensation drain.
Weight:	Dry weight (Lbs.): 290-395 (depending on platform)
Dimensions:	51.5W x 21.0L x 31.2H (In.) on 10 gallon air storage models 50.7W x 19.2L x 40.8H (In.) on 30 gallon air storage models 50.3W x 18.2L x 24.2H (In.) skid
Instrument Panel:	Panel to include 120V and 240V receptacles, volt meter, thermal breakers, generator on/off switch, welder connection and selector switch.
Drive System:	Heavy duty belt drive system with self-cooling, self-cleaning link belts to drive compressor. Belt is made of a custom-designed, high-tech polyurethane/polyester composite with an operating temperature range of -40 °F to +240 °F. Belt to drive the generators to be poly-V serpentine belt.

AIR N ARC® 150
ALL-IN-ONE POWER SYSTEM® 14 HP

Metal and Tanks:	Fully powder-coated with galvanneal sheet metal, 1/4" plate steel main frame, integrated lift hook and full-service access.
Warranty:	The air compressor, welder, generator unit shall be warranted for 3 years when following the prescribed maintenance schedule. This warranty does not cover damage caused by accident, misuse, or negligence. If the unit is disassembled the warranty is void.
Service Centers:	Manufacturer must have factory authorized service centers located in each state of the United States of America and Canadian provinces.
Options:	Cable Extensions – 20', 30', 40', 50' Remote Air Tank Options Remote Condensation Drain Welding Helmet with Auto Darkening Lens Dry Cell Battery Cold Weather Kits Maintenance Kits Hose Reels