



POWERFLEX™ AH
DIESEL DRIVEN ROTARY SCREW
AIR COMPRESSOR/
HYDRAULIC POWER PACK
BID SPECIFICATION
REVISED: July 22, 2025

Type:	Vanair® PowerFlex™ AH. In current production.
Compressor:	Vanair® encapsulated 40 CFM rotary screw air compressor system with clutch to eliminate horsepower consumption during unloaded condition.
Compressor Capacity:	40 CFM at up to 150 PSIG.
Air/Fluid Separator:	Separator to be externally mounted spin-on design. Vanair® separator shall provide for enhanced air quality, reduced operating and maintenance cost and optimized compressor performance.
Protective Circuit:	Compressor to automatically shutdown in case of high compressor temperature or over pressurization. Additional protective features provided include automatic blow down valve, compressor relief valve, air receiver relief valve and minimum pressure valve.
Cooling System:	Compressor cooling system shall allow rated air delivery and pressure operation continuously in 110°F ambient temperatures. Cooler to be mounted in a powder-coated galvaneal sheet metal enclosure with a blower type fan assembly. Compressor fluid shall be filtered by a 25 micron full flow spin-on replaceable filter canister. A thermal valve is included to regulate compressor cooling.
Inlet Controls:	Electric inlet control valve shall be integrated into compressor system and automatically modulate output from 0 to 100% in response to air demand.
Hydraulic Circuit:	Torque limiting variable displacement piston pump, capable of closed or open center hydraulic system. Output is up to 13 GPM maximum pressure output is 3000 PSI.
Truck/Body Interface:	Unit can be remotely started from crane remote. Unit ties to chassis battery to keep batteries charged when running safety and work lights. Unit designed to pull fuel from chassis fuel tank.
Engine:	Electric start diesel engine with automatic glow plugs, Kubota® model DH902, liquid cooled, tier 4 final 25 HP with high temperature and low oil pressure shut down. 60A alternator and energize to run fuel solenoid.
Fuel Capacity:	12 gallon slimline tank or tied to chassis.
Air Storage Tank:	4 gallon integrated
Weight:	Dry weight (Lbs.): 802
Dimensions:	47.6L x 21.0W x 33.4H (In.)
Instrument Panel:	Panel to have quick disconnects and be capable of being remotely mounted with use of optional factory harness. Panel to include engine start/stop function, hour meter, air compressor on/off switch and system fault lights, hydraulic on/off switch.

DIESEL DRIVEN ROTARY SCREW AIR COMPRESSOR/HYDRAULIC POWER PACK

Drive System:	Heavy duty belt-drive system. Belt to drive the hydraulic pump to be poly-V serpentine belt with quiet channel technology. Belt for compressor to be poly-V serpentine belt with quiet channel technology.
Metal and Tanks:	Fully powder-coated with galvalume sheet metal enclosure, 1/4" plate steel main frame, integrated lift hook and full-service access.
Warranty:	When following the prescribed maintenance schedule, the rotary screw compressor unit has a lifetime warranty by Vanair®. (NOTE: Engines are warranted separately by the engine manufacturer.) General, no wear components, are warranted for one (1) year. Consumable products such as filters are not covered. This warranty does not cover damage caused by accident, misuse or negligence. If the unit is disassembled the warranty is void.
Service Centers:	Manufacturer MUST have factory authorized service centers located in each state of the United States of America and Canadian provinces.
Cold Weather:	Includes 12V heater blankets for compressor inlet valve, engine oil pan, compressor sump and hydraulic tank.
Options:	Remote Control Panel Maintenance Kits Air Hoses, Hose Reels and Fittings OSHA Safety Valve (Velocity Fuse) Filter/Lubricator/Regulator (FLR) Battery Harness Air Reservoirs Service/Control Line Moisture Separators Tool Oiler/Lubricator Air Aftercooler