



Designed to eliminate the backbreaking labor of loading and unloading your crew's tools, Vanair's ETL-350* and ETL-500 electric tool lift handles up to three pneumatic tools with no problem. With our electric tool lift, your tools are securely transported to the jobsite, where they are safely lifted from the truck to ground level. Both the ETL-350* and ETL-500 eliminate the hassle of a hydraulic system by being powered by the vehicle's battery. Because our actuator has a compact design it is easily incorporated into the frame of the lift, providing more room in the bed of your vehicle.

ETL FEATURES

- Three integrated tool holder positions
- Integrated limit switches
- Various hex tool posts ranging from 7/8" to 1-1/4"
- Integrated actuator brake allows load to be stopped in any position
- Safeties: integrated actuator overload clutch, safety latch, and integrated safety shut-off switch



ETL-350*



ETL-500

POWER SUPPLY SPECIFICATIONS

Linear Actuator	12VDC ball screw motor with 30A maximum current draw
Maximum Stroke Speed	2.7 inches per second
Temperature Range	-40°F – 140°F, IP65 rated
Operating Voltage Range	10VDC – 16VDC (Ratings at 12VDC normal) with built-in thermal overload control

DIMENSION SPECIFICATIONS

ETL-350*		ETL-500
32.9"	Height	47.5"
17.5"	Width	17.5"
16.1"	Depth Folded	16.6"
35.2"	Maximum Reach	35.2"
17.6"	Maximum Drop	35.0"
150 lbs.	Weight	225 lbs.
350 lbs. Max**	Lifting Capacity	500 lbs. Max**

* The ETL-350 is special order only.

** Lifting Capacity is derated based on tilt angle.

Vanair® reserves the right to make changes in engineering, design, and specifications, add improvements, or discontinue manufacturing at any time, without notice or obligation. Vanair®, the Vanair® logo and MOBILE POWER SOLUTIONS® are registered trademarks or trademarks of Vanair®, a Lincoln Electric Company, Michigan City, IN, USA. © 2026 All Rights Reserved.



VANAIR®
A Lincoln Electric Company

800.526.8817 | vanair.com